

ZY8520

High-efficiency
Energy-saving
Ceiling Light



Applications

This product is widely applicable to the illumination for the stations, large factories, supermarkets, warehouses and stadiums.

Features

- The reflector uses the diamond surface, mirror surface or frosted surface, which is particularly used for fixed illumination for places with high sheds or ceilings.

Different reflectors are to be chosen upon the needs of the specific environment:

Diamond surface: it uses imported high purity aluminum sheet, with high reflection rate. The special angle design is conducive to raise the illumination effects, remove dazzling light and contribute to even and gentle light projection.

Mirror surface: it uses imported high purity aluminum sheet, with high reflection rate of parabola design and small angle of light projection.

Frosted surface: it uses imported high purity aluminum sheet, with high reflection rate of frosted surface design, and even and gentle light projection

- With integrated structure design, it is installed and used more conveniently.
- Its lighting source and electrical components are of famous brands from Germany, with long service life and reliable performance, the brightness 10%~20% higher than those of same products, free of the troubles and inconveniences for frequent changes of bulbs.
- Special structure design and excellent materials keep it from the dust, corrosion, rain, or rusting.
- The tempered glass is used as transparent part, which can withstand impact or corrosion.
- The electrical cabinet boasts good heat radiation, and can radiate the heat produced from the bulb and ballast rapidly, and prevent the electric fittings from damaging due to the high temperature in the ballast box.
- It is mounted in suspension or fastening, which is safe, simple and convenient.





Frosted surface

Mirror surface

Lighting Source

Order Number	Lighting source	Rated power(W)	Luminous flux(Lm)	Average service life(h)
ZY8520-J250	MH gas discharge lamp	250	21000	9000
ZY8520-J400	MH gas discharge lamp	400	36000	9000
ZY8520-N250	HPS gas discharge lamp	250	27500	27500
ZY8520-N400	HPS gas discharge lamp	400	50000	27500
ZY8520A-TJ150	Ceramic metal halide lamp	150	13500	10000
ZY8520A-TJ250	Ceramic metal halide lamp	250	21500	10000

Light Distribution Curve



Product Data

Rated voltage	AC220V 50Hz
Insulation grade	I
Drop cable	φ 10mm ~ φ 14mm
Dimension of lamp(mm)	φ 452 × 638
Package size (mm)	520 × 520 × 700
Net weight	11Kg
Gross weight	13.5Kg

Dimension And Mounting Mode

